

Durability with a classic touch.

Available in base plate and embedded styles.

Features and Benefits

- Prestressed steel and highest quality concrete are centrifugally cast for ultimate strength and long-term durability
- Natural stone and terrazzo aggregates maintain a like new appearance with virtually no maintenance
- Conforms to applicable sections of ACI, AASHTO, ASTM and PCI standards
- Exclusive 10-year warranty

Colors and Finishes

A wide range of standard, pre-formulated and custom colors are available. The concrete shafts are lightly blasted to expose the texture and beauty of the natural stone. See separate Aggregates and Finishes sheet for details. We offer Amerishield $^{\text{TM}}$, a premium graffiti-resistant coating, as well as other durable sealers and protectants that further enhance colors, protect the concrete surface and aid in the removal of graffiti.

Victorian III Pole

Eight crisp, sharp flowing lines, a flared base and the tapered shaft are reminiscent of the gas lamp era. Victorian III works well with traditional and contemporary architectural designs.

Our Victorian Series lighting poles combine the charm of yesterday with the technology of today. Available in a variety of configurations, colors and finishes, the Victorian series provides architects and designers with many creative options.



Victorian III - Base plate style information


Catalog Number	Pole Height "A"	Top OD	Base OD	Anchor Bolt	Bolt Circle	Base Plate (Sq)	Ultimate G.L. Moment	Pole Weight
VBO03.0	9'-10"	7½"	18"	³ / ₄ " x 24"x 4"	21"	20"	22,500 ft lbs	720lbs
VB003.7	12'-2"	7½"	18"	³ / ₄ " x 24" x 4"	21"	20"	22,500 ft lbs	875 lbs
VBO04.5	14' -9"	7½"	18"	³ / ₄ " × 24"× 4"	21"	20"	22,500 ft lbs	1,000lbs
VBO04.8	1'-9"	6¾"	18 "	³ / ₄ " × 24"× 4"	21"	20"	22,500 ft lbs	1,100 lbs
VB005.5	18'-0"	6¾"	18 "	³ / ₄ " × 24"× 4"	21"	20"	22,500 ft lbs	1,300 lbs
VBO06.3	20'-8"	6¾"	18 "	³ / ₄ " × 24"× 4"	21"	20"	22,500 ft lbs	1,400 lbs
VBO09.0	29'-6"	5%"	18 "	³ / ₄ " × 24"× 4"	21"	20"	22,500 ft lbs	1,850 lbs
VBOX10.5	34'-6"	5%"	18"	³ / ₄ " x 24"x 4"	21"	20"	32,000 ft lbs	2,200lbs

Top OD across the flats


Ollbs Ollbs

Victorian III - Embedded style information


Catalog Number	Pole Height "A"	Top OD	Base OD	Embedded Depth "B"	Overall Length "OL"	Ultimate G.L. Moment	Pole Weight
VEO03.0	9'-10"	7½"	18"	5'-0"	14'-10"	22,500 ft lbs	900 lbs
VEO03.7	1'-2"	7½"	18"	5'-0"	17' -2"	22,500 ft lbs	1,050 lbs
VEO04.5	14'-9"	7½"	18"	5'-0"	19'-9"	22,500 ft lbs	1,100 lbs
VEO04.8	15 '-9"	6¾"	18"	5'-0"	20'-9"	22,500 ft lbs	1,200 lbs
VEO05.5	18'-0"	6¾"	18"	5'-0"	23'-0"	22,500 ft lbs	1,450 lbs
VEO06.3	20'-8"	6¾"	18"	5'-0"	25'-8"	22,500 ft lbs	1,500 lbs
VEO09.0	29'-6"	5%"	18"	5'-0"	34'-6"	22,500 ft lbs	2,000 lbs
VEOX10.5	34'-6"	51/8"	18"	5'-0"	39'-6"	32,000 ft lbs	2,300 lbs




"capping detail"



Share cross section detail



Slotted base plate prestressed to pole



"A"

"OL"

Specifications - Use Centrecon specifications

Colors and finishes - See Centrecon color selection guide

Luminaire mounting - See mounting options section for more information

Anti-graffiti and sealer - Optional coatings are available for added protection



Double

cable

entrances